

Calibration Routines for KODAK PROFESSIONAL ENDURA Premier Metallic Paper

Kodak

CURRENT INFORMATION SUMMARY

January 2012 • CIS-290

GENERAL INFORMATION

KODAK PROFESSIONAL ENDURA Premier Metallic Paper is optimized for digital printers. Significant testing has been done across a broad range of Kodak Professional and other manufacturers' digital printers to validate satisfactory digital performance of KODAK PROFESSIONAL ENDURA Premier Metallic Paper.

Kodak's Printer Calibrations for KODAK PROFESSIONAL ENDURA Premier Metallic Paper

To achieve optimal quality prints on KODAK PROFESSIONAL ENDURA Premier Metallic Paper with Kodak digital output devices such as the KODAK PROFESSIONAL Digital Multiprinter or the KODAK PROFESSIONAL LED II Printer, you must install new calibration files.

The latest calibration files for Windows NT and 2000 (V4.3) and Macintosh (V4.3) operating systems are available at www.kodak.com/go/propapersupport. If your printer does not have the newest calibration files, download and install them at this time. These files currently support:

LED and laser printers, including:

- KODAK PROFESSIONAL RR 30 Laser Printer
- KODAK PROFESSIONAL RP 30 and SRP 30 Laser Printers
- KODAK PROFESSIONAL RP 50 LED Printer
- KODAK PROFESSIONAL LED II Printers 20R and 20P
- KODAK PROFESSIONAL LED Digital Color Printers 20R and 20P

CRT printers, including:

- KODAK PROFESSIONAL Digital Multiprinters (KPDM & KPDM II)
- KODAK DIGITAL SCIENCE LF CRT Color Printer
- KODAK 4" CRT Color Printer

Note: New ICC output profiles are also recommended for ENDURA Premier Metallic Paper because of its greater color gamut. ICC output profiles can be found at www.kodak.com/go/colorprofiles.

Other Equipment Manufacturer's Printer Calibration for KODAK PROFESSIONAL ENDURA Premier Metallic Paper

The starting-point recommendations listed in the following table have yielded good image quality in prints on KODAK PROFESSIONAL ENDURA Premier Metallic Paper produced by other equipment manufacturers' digital output devices.

Calibration Routines for KODAK PROFESSIONAL ENDURA Premier Metallic Paper

Printer	Calibration
Oce LightJet 430 and 5000	<ol style="list-style-type: none"> 1. Go to the Oce FTP Site at www.dgs.oce.com/PrinterSupport/LJ_Customer_Access. 2. Read the "Lightjet Media Read Me" document for information regarding downloading printer aims. 3. Select the link to the Media Targets for your Lightjet printer. 4. Download the appropriate aim files, as directed in the read-me file.
Durst Lambda 130 and 76+	Starting D-max: 2.30R, 2.20G, 2.20B (It is possible to obtain higher D-max in images that do not include text.) Basic Calibration settings: Y=91.70, M=81.90, C=0.00, D=116.9
Durst Epsilon 30	For best results, select HIQ or SIQ mode. Starting D-max: 2.30R, 2.20G, 2.15B Basic Calibration settings: D=0.967, C=0.000, M=0.203, Y=0.159
Durst Theta 76	Starting D-max: 2.25R, 2.20G, 2.15B, Basic Calibration settings: D=1.452, C=0, M=0.012, Y=0.154
Durst Theta 50/51	Starting D-max: 2.30R, 2.20G, 2.20B Basic Calibration settings: D=131.00, C=0.0, M=87.00, Y=140.00
Durst Zeta	Please contact your Durst service representative for the file.
Fuji Frontier	We recommend that you use KODAK PROFESSIONAL ENDURA Premier Metallic Paper to calibrate the printer channel that you plan to use. If you don't have a recommended channel that you normally use, please start testing with Channel I. <ol style="list-style-type: none"> 1. Load ENDURA Premier Metallic Paper into the paper magazine that you will use to print. 2. From the Setup and Maintenance menu, select Print Condition Setup and Check. Then select Paper Condition Setup to perform a standard calibration.
Noritsu QSS-2711 and Noritsu MP1600	Setting up a Channel for KODAK PROFESSIONAL ENDURA Premier Metallic Paper <ol style="list-style-type: none"> 1. Set up a paper channel with ENDURA Premier Metallic Paper, using the normal Setup procedure. This setup includes MLVA Setup, Uniformity, and Gamma tests. 2. If any color changes are needed, enter them using the Magazine Balance function on the NORITSU MP1600 printer.
Noritsu QSS 31XX, 32XX, 33XX, 34XX, and R2R printers	<ol style="list-style-type: none"> 1. Contact Noritsu for the software which contains the profile data for KODAK PROFESSIONAL ENDURA Premier Paper. 2. If profile data is not available from Noritsu, use the Supra VC channel. Calibrate using the "Registering a New Paper Type and Setup" procedure. Refer to your Noritsu manual.
Polielettronica LASERLAB	<ol style="list-style-type: none"> 1. Set these starting Laser Maximum Density values: Y=257, M=236, C=191. 2. Starting Color Compensation Values Y=0.93, M=0.84, C=0.97. 3. Proceed with the manufacturer's standard paper calibration procedure.
Gretag Netprinter	Basic Data required for calibration are available from Gretag Imaging.
Sienna Mileca HSP	Basic Data required for calibration are available from Sienna Imaging.
ZBE Chromira	Select Kodak on the Emulsion menu, and enter: D-max Aim: 2.40R, 2.35G, 2.30B Starting Calibration Values: (C) 0, (M) 47, (Y) -45, (D) -22 Then follow the standard paper calibration procedure.

Kodak, Kodak Professional, Endura, and Supra are trademarks.

Revised 01-12

Calibration Routines for KODAK
PROFESSIONAL ENDURA Premier
Metallic Paper
KODAK Publication No. CIS-290

Paper and Output Systems
EASTMAN KODAK COMPANY • ROCHESTER, NY 14650

Kodak