

Print even more possibilities.

Introducing the all-in-one **Kodak Moments 6950 Photo Printer** with brand-new cutting and slitting capabilities. Enjoy a new portfolio of print sizes with the capability to print full-bleed sizes from 2 to 20 inches. Based on the design of the robust **Kodak 6900 Printer**, this new model expands the print product offering for even more profit potential. From trendy Mini Prints to impactful Panoramic Prints, trusted **Kodak Moments** printing quality ensures that your customers' photos last.

More full-bleed printing capabilities.

- Full-bleed 5 and 6 inch printing with one 6R media kit.
- No 5R hardware, extra accessories or media kits needed to customize prints.

Increased efficiency with two print modes for speed and quality.

- Standard Mode produces classic 4x6 prints in under 14 seconds each.
- High Quality Mode produces beautiful gloss or matte prints.

Includes all the same innovative features from the Kodak 6900 Printer.

- Increased usability and convenience with a lighter, smaller footprint.
- Front loading feature enables ease of printer handling and serviceability.
- Ideal for use by retailers, photographers and photo studios for high volume printing, even imaging and photo booths.
- Designed to fit inside new **Kodak Moments** cabinetry.

Compatible with Kodak 6900 media.



Printer Specifications	
Printing technology	Thermal dye sublimation
Printing resolution	300 dpi (continuous tone)
Output sizes	2x6" (5x15 cm), 3x6" (8x15 cm) 4x6" (10x15 cm), 6x6" (15x15 cm) 6x8" (15x20 cm), 6x12" (15x30 cm) 6x14" (15x36 cm), 6x18" (15x46 cm) 6x20" (15x51 cm), 3.5x5" (9x13cm) 5x5" (13x13 cm), 5x7" (13x18 cm)
Print speed (Standard Mode)	13.45 seconds for 4x6" (10x15 cm)
Print speed (High Quality Mode)	22.53 seconds for 4x6" (10x15 cm)
Media Format & Capacity	
Media format: Roll	4x6" (10x15 cm): up to 750 capacity 6x8" (15x20 cm): up to 375 capacity 6x20" (15x51 cm): up to 125 capacity 5x7" (13x18 cm): up to 375 capacity
Printer Physical Characteristics	
Dimensions (H x W x D)	14" x 11" x 18" (36 x 28 x 46 cm)
Weight (Does not include media)	40 lb. (18 kg)
Operating Requirements	
Power & Consumption	Voltage: 100 - 240V AC Current: Shall not exceed 5.5A @ 100 VAC or 2.4A @ 240V Frequency: 50/60 Hz
Operating temperature range	59 - 95°F (15-35°C)
Relative humidity	20 to 90% non-condensing

Regulatory/Compliance

Emissions	US FCC Part 15 (FCC Mark), Canada IEC-003 (A), EMC Directive (CE Mark), Australia RCM
Safety	US-UL, Canada-UL, EU Low Voltage Directive (CE Mark), Australia RCM
RFID	FCC ID, Canada IC ID, Australia RCM, EU Radio Equipment Directive (CE Mark)

Patents

US Patent Numbers	6,961,075; 7,852,359; 7,400,337; 7,397,489 and other patents pending.
-------------------	---

Computer Information & Software Requirements

Computer & Printer Interface	USB 2.0 (compatible with USB 1.1)
Required Kodak Kiosk Software	Kodak Picture Kiosk Software Version 11.0 or higher, available separately
Service	Kodak Advanced Unit Replacement (AUR) support available

Ordering Information

Printers & Hardware

	CAT No.
Kodak Moments 6950 Photo Printer 230V	1070085
Kodak Moments 6950 Photo Printer 120V	1070101
Kodak Moments 6950 Photo Printer Conversion Kit/5R	1073782

Compatible Consumables

Kodak Photo Print Kit 6900/6800/6R
Kodak Photo Paper 6900/6800/6R
Kodak Photo Ribbon 6900/6800/6R

For more information contact your local **Kodak Moments** representative or visit kodakalaris.com.