

Expected reliability with upgraded performance.

Introducing a versatile printer reinvigorated with powerful performance upgrades. Customers can enjoy creating a wide range of premium products, including flat and folded greeting cards, photo books, calendars and **Kodak** Copy Service products, with all-new speed and ease.

- Enjoy optimized photo printing on various substrates such as photo book and card stock paper.
- An updated double media tray configuration offers the convenience of holding various paper stocks so clerks don't need to switch trays. A third tray is available as an accessory for additional cost.
- Works seamlessly with **Kodak** Adaptive Picture Exchange (APEX) Systems* and uses **Kodak** ICC profiles, which allow for closer color matching from screen to print output.
- All-new toners and formulas deliver excellent color reproduction and robust fusing characteristics. The new toners are backwards compatible with **Kodak** DL2100 Photo Printer.

Printer Package Contents	
DL2200 Duplex Printer	120V or 230V Printer, Print Tray Assembly and Block for Printer Tray
Printer Specifications	
Printing Technology	Single Pass LED Electro Photographic Printer
Printing Resolution	600 dpi (continuous tone)
Output Sizes	
Duplex Paper - Letter	8.5 x 11" (21.6 x 28.9 cm)
Duplex Paper - A4	8.3 x 11.7" (21.0 x 29.7cm)
Duplex Card Stock - Folded	4.8 x 6.8" (12.2 x 17.3 cm)
Duplex Card Stock - Flat	4.8 x 6.8" (12.2 x 17.3 cm)
Copy / Print Paper - A4	8.3 x 11.7" (21.0 x 29.7cm)
Print Speed	10 seconds for flat or folded greeting card 5 minutes for 10 page duplex photo book
Media Format & Capacity	
Duplex Paper - Letter	250 sheets
Duplex Paper - A4	250 sheets
Duplex Card Stock - Folded	2 packs of 100 card sheets
Duplex Card Stock - Flat	2 packs of 200 card sheets, 2 cards per perforated sheet
Printer Physical Characteristics	
Dimensions: height x width x depth	15 x 17 x 24" (38.1 x 43.2 x 61 cm)
Weight: (does not include media)	68 lbs. (31 kg)
Operating Requirements	
Power Consumption	Standby Average: 100W
Operation Max	1300W
Operating temperature range	50 - 90°F (10 - 32°C)
Relative Humidity	20 to 80%, non-condensing

Contact your local **Kodak Moments** representative for more information, or visit www.kodakalaris.com



Regulatory and Compliance

Emissions	US FCC Part 15 (FCC Mark) EU Radio Equipment and EMC Directive (CE Mark)
Safety	US-UL, EU Low Voltage Directive (CE Mark)

Computer Information

Computer and Printer Interface	USB 1.1
Required Software	Kodak Picture Kiosk Software Version 7.0 or higher, available separately.

Service

Kodak Advanced Unit Replacement (AUR) support available

Ordering Information	CAT No.
DL2200 Duplex Printer 120V with Tray Assembly	1023381
DL2200 Duplex Printer 230V with Tray Assembly	1023407
DL2200/DL2100 Printer Media Tray	1023456

Compatible Consumables

Toner	
DL2200/DL2100 Duplex Printer Toner / Black	1023324
DL2200/DL2100 Duplex Printer Toner / Cyan	1023274
DL2200/DL2100 Duplex Printer Toner / Magenta	1023282
DL2200/DL2100 Duplex Printer Toner / Yellow	1023316

Paper

Kodak DL2200/DL2100 Duplex Paper / Letter	8851875
Kodak DL2200/DL2100 Duplex Paper / A4	1904267
Kodak DL2200/DL2100 Duplex Card Stock / Folded	8433260
Kodak DL2200/DL2100 Duplex Card Stock / Flat	8002420